

II. Listing of Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-44. (Canceled)

45. (Previously Presented) A coupling assembly for joining a power source to a medical dissection tool, the coupling assembly comprising:

a coupling shaft having a proximal portion, an opposing distal portion, and a longitudinal axis extending therebetween, wherein the distal portion comprises an external surface and an internal surface, the internal surface defining a bore extending along the longitudinal axis for receiving a portion of the medical dissection tool,

a first aperture extending from the external surface to the internal surface along a first axis substantially perpendicular to the longitudinal axis, the first aperture having a first length extending substantially along the longitudinal axis between a proximal wall and a distal wall, the first aperture having a first width extending substantially transverse to both the longitudinal axis and the first axis between a pair of sidewalls, wherein the first length is greater than the first width such that the first aperture is elongated along the longitudinal axis and wherein the proximal wall, distal wall, and pair of sidewalls extend in a direction substantially parallel to the first axis;

a first locking member positioned at least partially within the first aperture and translatable along the longitudinal axis with respect to the coupling shaft from an unlocked position to a locked position to secure the medical dissection tool within the internal passage, wherein the first locking member is spaced from the proximal wall of the first aperture and adjacent to the distal wall of the first aperture in the unlocked position and wherein the first locking member is adjacent to the proximal wall of the first aperture and spaced from the distal wall of the first aperture in the locked position;

an engagement sleeve disposed around the distal portion of the coupling shaft, the engagement sleeve having an internal contact surface for engagement with the first locking member, the internal contact surface extending at an oblique angle with respect to the longitudinal axis;

a spring biasing the engagement sleeve towards the proximal portion of the coupling shaft; and

an attachment housing disposed around the proximal portion of the coupling shaft for controlling the position of the engagement sleeve relative to the coupling shaft, the attachment housing moveable along the longitudinal axis relative to the coupling shaft by rotation of the attachment housing about the longitudinal axis;

wherein the first locking member translates at an oblique angle relative to the longitudinal axis and the first axis when moved between the unlocked and locked positions.

46. (Previously Presented) The coupling assembly of claim 45, wherein the oblique angle is approximately 45°.

47. (Previously Presented) The coupling assembly of claim 45, wherein the first locking member comprises a spherical ball.

48. (Previously Presented) The coupling assembly of claim 45, further comprising a second aperture extending from the external surface to the internal surface along a second axis substantially perpendicular to the longitudinal axis, the second aperture having a second length extending substantially along the longitudinal axis and a second width extending substantially transverse to both the longitudinal axis and the second axis, wherein the second length is greater than the second width such that the second aperture is elongated along the longitudinal axis.

49. (Previously Presented) The coupling assembly of claim 48, further comprising a second locking member positioned at least partially within the second aperture and translatable along the longitudinal axis with respect to the coupling shaft from an unlocked positioned to a locked position to secure the medical dissection tool within the internal passage.

50. (Previously Presented) The coupling assembly of claim 49, wherein the second locking member translates at an oblique angle relative to the longitudinal axis and the second axis when moved between the unlocked and locked positions.

51. (Previously Presented) The coupling assembly of claim 49, wherein a portion of the internal contact surface of the engagement sleeve is configured for engagement with the second locking member.

52. (Previously Presented) The coupling assembly of claim 48, further comprising a third aperture extending from the external surface to the internal surface along a third axis substantially perpendicular to the longitudinal axis, the third aperture having a third length extending substantially along the longitudinal axis and a third width extending substantially transverse to both the longitudinal axis and the second axis, wherein the third length is greater than the third width such that the second aperture is elongated along the longitudinal axis.

53. (Previously Presented) The coupling assembly of claim 52, further comprising a third locking member positioned at least partially within the third aperture and translatable along the longitudinal axis with respect to the coupling shaft from an unlocked position to a locked position to secure the medical dissection tool within the internal passage.

54. (Previously Presented) The coupling assembly of claim 45, wherein the second and third locking members each comprise a spherical ball.